



INNOSMART EY

LED BULB

LED Life Time:
> 50,000 h

Type: Indoor/Domestic

Body Color : White

Dimension



*Dimensions are given in the table below. All measurements are in mm

Product Information

Light Source	Everlight
Color Temperature	3000K/4000K/6500K
Efficacy	100-110 Lm/W
SDCM Binning	<5

Electrical Data

Power Supply	Hansa Green
Input Voltage	AC 110~240 V
Input frequency	50-60 Hz
Power Factor	>0.5
Efficiency	>90%
THD	<15%

General

Housing & Optics	Composite Alluminium & PC Diffuser
Ambient Temperature	-25°C to 50°C
Storage Temperature	-40°C to 50°C
Humidity	RH 10% - 90%
Safety Features	Open Circuit, Short Circuit & Over Voltage Protection
IP Rating	IP20

Model No.	Power (W)	Lumens	CCT	CRI	Beam Angle	Dimension (mm)
LCB-03-B22	3 W	300lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 44 mm, Ht: 80 mm
LCB-05-B22	5 W	500lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 47 mm, Ht: 85 mm
LCB-07-B22	7 W	700lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 56 mm, Ht: 105 mm
LCB-09-B22	9W	900lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 56 mm, Ht: 105 mm
LCB-12-B22	12W	1200lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 60 mm, Ht:122 mm
LCB-15-B22	15W	1500lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 65 mm, Ht: 135 mm
LCB-18-B22	18W	1800lm±10%	3000K/4000K / 6500K	>70	120°	Dia: 72 mm, Ht: 145 mm

