




STEFANO 40W SDL-CB-40





 Luminaire shape

 Body color

 Die cast Aluminium Body

 IP44 Rated

 IP20 Rated Control gear

 50000 Hrs Lifetime


Stefano is a versatile recessed down light that can be used widely in indoors, easy to mount on the ceiling recess. The luminaire offering a broad range of power, color temperatures and options like motion detection, timer, sleep and twilight function.

This range of products are popular for a wide range of application such as office spaces, Conference Halls, Foyers, Shops, residential and other indoor spaces.

Luminaire Details:





Product Name	: Stefano
Product Type	: LED Recessed Down Light
Product code	: SDL-CB-40
Efficiency Classification	: Class B
Luminaire Type	: COB
Fixture Type	: Fixed

Correlated Color Temperature:



Light Source Details:

Light Emission	: Spot Emission
Source brand	: Everlight
Rated Power	: 40 W
CRI	: >80
UGR	: <19
McAdam Binning	: Step 3

CCT	Rated Lumens
 3000K	3600 lms
 4000K	3800 lms
 5000K	4000 lms
 6500K	4400 lms

Luminaire Housing:

Body	: Die cast Aluminium
Reflector type	: PC Faceted Reflector
Lens/Diffuser	: TIR Lens
Storage Temperature (Ts)	: -40 to 60°C
Ambient Temperature (Ta)	: -20 to 50°C
Humidity	: RH 10-90 %

5 Years Product Warranty

Control Gear Specifications:

Control Gear Brand	: Hansa Green
Input Voltage	: 220-240V AC
Input Current	: 0.16A
Frequency	: 50/60Hz
Output Voltage	: 25-45V DC Max.
Output Current	: 1050 mA
Max. Output power	: 45W
Power Factor	: >0.9
THD	: <15%
Case temperature(Tc)	: 80°C
Ambient Temperature	: -20 to 60 C
Over voltage protection	: Available
Short circuit Protection	: Available
No-Load Protection	: Available
Burst Protection Voltage	: 1KV
Surge Protection Voltage	: 1KV(L to N) & 2KV(L/N to Earth)



Control Gear Compatibility:

Control Gear is the driving unit of LED. Stefano is compatible with Phase cut dimming, 0-10/1-10V dimming and DALI Dimming control gears.



Optics and Beam Angle:

20°, 40°, 60° Optics



Add-on sensor Compatibility:



Stefano is compatible with external add-on motion detection and daylight sensors.


Photometric Details:

Photometric testing provides a comprehensive laboratory service for testing the amount, colour, quality and spatial distribution of light emitted from lamps, LEDs and luminaires. The standard photometric data files in IES (.ies) and EULUMDAT (.ldt) formats per IES LM 79-08 and BS EN 13032



Emergency Compatibility:

Stefano is compatible with emergency kits



Physical Dimensions:



Ordering Codes

CCT	Code
3000K	629053040521
4000K	629053040541
5000K	629053040561
6500K	629053040591

Diameter	: 200 mm
Height	: 90 mm
Cut out	: 180 mm