



NEGOZIO BOX GIMBAL-BGX3 -3*20W BG3-20





 Luminaire Shape

  Frame Color

 Die cast Aluminium Body

 IP44 Rated

 IP20 Rated Control gear

 50000 Hrs Lifetime


Negozio Box Gimbal is a versatile recessed spot light that can be used widely in indoors, easy to mount on the ceiling recess. The luminaire offering a broad range of power,color temperatures and options like motion detection, timer, sleep and twilight function.

This range of products are popular for a wide range of application such as Retail Showrooms,Galleries,Exhibition Halls, Shopping Malls and other indoor spaces.

Luminaire Details:





Product Name	: Negozio Box Gimbal-BGX3
Product Type	: LED Recessed Gimbal Light
Product code	: BG3-20
Efficiency Classification	: Class B
Luminaire Type	: COB
Fixture Type	: Adjustable

Correlated Color Temperature:



Light Source Details:

Light Emission	: Spot Emission
Source brand	: Cree
Rated Power	: 3*20 W
CRI	: >80
UGR	: <19
McAdam Binning	: Step 3

CCT	Rated Lumens
 3000K	5400 lms
 4000K	5700 lms
 5000K	6000 lms
 6500K	6300 lms

Luminaire Housing:

Body	: Die cast Aluminium
Reflector type	: Aluminium Reflector
Lens/Diffuser	: Glass Diffuser
Storage Temperature (Ts)	: -40 to 60°C
Ambient Temperature (Ta)	: -20 to 50°C
Humidity	: RH 10-90 %

5 Years Product Warranty

Control Gear Specifications:

Control Gear Brand	: Hansa Green
Input Voltage	: 220-240V AC
Input Current	: 0.083A
Frequency	: 50/60Hz
Output Voltage	: 36-72 V DC Max.
Output Current	: 300 mA
Max. Output power	: 22W
Power Factor	: >0.9
THD	: <15%
Case temperature(Tc)	: 80°C
Ambient Temperature	: -20 to 60 C
Over voltage protection	: Available
Short circuit Protection	: Available
No-Load Protection	: Available
Burst Protection Voltage	: 1KV
Surge Protection Voltage	: 1KV(L to N) & 2KV(L/N to Earth)

Control Gear Compatibility:

Control Gear is the driving unit of LED. Negozio Box Gimbal is compatible with Phase cut dimming, 0-10/1-10V dimming and DALI Dimming control gears.



Optics and Beam Angle:

24°, 60° Optics

Add-on sensor Compatibility:




Negozio Box Gimbal is compatible with external add-on motion detection and daylight sensors.

Photometric Details:


Photometric testing provides a comprehensive laboratory service for testing the amount, colour, quality and spatial distribution of light emitted from lamps, LEDs and luminaires. The standard photometric data files in IES (.ies) and EULUMDAT (.ldt) formats per IES LM 79-08 and BS EN 13032

Emergency Compatibility:

Negozio Box Gimbal is compatible with emergency kits



Physical Dimensions:



Length	: 415*165 mm
Height	: 135 mm
Cut out	: 405*155 mm

Ordering Codes

CCT	Code
3000K	629062020521
4000K	629062020541
5000K	629062020561
6500K	629062020591