



## BOLLAX 360



 +971 65 260 706     [sales-me@hansagreen.com](mailto:sales-me@hansagreen.com)

 Hamriyah Free Zone Sharjah, UAE.

# BOLLAX 360 7W

## LED BOLLARD LIGHT

- Uniform **360°** Illumination – Even all-around lighting.
- Corrosion-resistant body - Ensures long-lasting durability.
- Long life: 50,000+ hrs - Minimal maintenance.
- Quick & easy installation - with accessible mounting design.
- Consistent Performance & Quality - Delivers stable brightness.




### BOL-360-07

Technical		IK08	IP65	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			Clear Acrylic		
Reflector			-		
Mounting			Surface		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

## ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Hansagreen/Tridonic		On/off	
Rated Power	07	Watts		
Input Current (@ 230V)	0.03	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	300	mA		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

## DIMENSIONAL DETAILS



All measurements are in mm

D	L	W	Cutout	Weight
86 $\phi$	600	126	-	1.55 kg

## PHOTOMETRIC DETAILS

Beam Angle	81.7°
------------	-------

