



PICASSO SLICK



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

PICASSO SLICK 12W

LED LINEAR FAÇADE LIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Adjustable Beam Angles – provides flexible light distribution.
- ❑ Consistent Performance & Quality - Delivers stable brightness
- ❑ IP65 Rated – protects against dust and water.



PSL-SNG-0.5-12

Technical		IK10	IP66	UGR <19	CRI >80
Light Source		SMD		Bridgelux	
Luminous Efficacy (subject to a tolerance of $\pm 10\%$)		100		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		Aluminium		Die-cast	
Lens / Diffuser		PC Lens		Toughened Glass	
Reflector		-			
Mounting		Surface			
Thermal					
Ambient Temperature (Ta)		-20 to 50		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Hansagreen		On/off	
Rated Power	12		Watts	
Input Current (@ 230V)	0.043		Amps	
Input Voltage	220 to 240		VAC	
Frequency	50 to 60		Hertz	
Output Current	300		mA	
Output Voltage	21 to 42		VDC	
Power Factor	>0.85			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
500	38	27	-	0.6 kg

PHOTOMETRIC DETAILS

Beam Angle	19.9°
------------	-------

