



PICASSO SLICK



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

PICASSO SLICK 15W

LED LINEAR FAÇADE LIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Adjustable Beam Angles – provides flexible light distribution.
- ❑ Consistent Performance & Quality - Delivers stable brightness
- ❑ IP65 Rated – protects against dust and water.



PSL-SNG-1.0-15

Technical	IK10	IP66	UGR <19	CRI >80
Light Source		SMD	-	
Luminous Efficacy (subject to a tolerance of ±10%)		100		Lumen / Watt
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin
Lifetime		50,000		Hours
McAdam Binning		3		Step
Housing				
Body		Aluminium		Die-cast
Lens / Diffuser		PC Lens		Toughened Glass
Reflector		-		
Mounting		Surface		
Thermal				
Ambient Temperature (Ta)		-20 to 50		°Celsius
Storage Temperature (Ts)		-20 to 50		°Celsius
Humidity		10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Control Brand	Hansagreen	On/off
Rated Power	15	Watts
Input Current (@ 230V)	0.065	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	400	mA
Output Voltage	21 to 42	VDC
Power Factor	>0.85	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
1003	38	27	-	1.35 kg

PHOTOMETRIC DETAILS

Beam Angle	19.9°
------------	-------

