



SOLACE SOLID



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

SOLACE SOLID 30W

LED BULKHEAD LIGHT

- High Luminous Efficacy - More light output
- Long Life: 50,000 hrs - Minimal maintenance
- Consistent Performance & Quality - Delivers stable brightness
- Diffused Illumination – Soft, uniform, glare-free light.
- IP65 Rated – Protection against dust and water.




BLK-SS-30

Technical		IK09	IP65	UGR <19	CRI >80
Light Source			SMD	-	
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			PC Diffuser		
Reflector			-		
Mounting			Surface		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Control Brand	Tridonic	On/off
Rated Power	30	Watts
Input Current (@ 230V)	0.13	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	800	mA
Output Voltage	24 to 42	VDC
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
275Ø	-	83	-	1.06 kg

PHOTOMETRIC DETAILS

Beam Angle	110.5°
------------	--------

