



SOLACE SOLID



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

SOLACE SOLID 36W

LED BULKHEAD LIGHT

- ❑ High Luminous Efficacy - More light output
- ❑ Long Life: 50,000 hrs - Minimal maintenance
- ❑ Consistent Performance & Quality - Delivers stable brightness
- ❑ Diffused Illumination – Soft, uniform, glare-free light.
- ❑ IP65 Rated – Protection against dust and water.




BLK-SS-36

Technical			IK09	IP65	UGR <19	CRI ≥80
Light Source				SMD		-
Luminous Efficacy (subject to a tolerance of ±10%)				100		Lumen / Watt
Correlated Colour Temperature (CCT)				3000/4000/6500		Kelvin
Lifetime				50,000		Hours
McAdam Binning				3		Step
Housing						
Body				Aluminium		Die-cast
Lens / Diffuser				PC Diffuser		
Reflector				-		
Mounting				Surface		
Thermal						
Ambient Temperature (Ta)				-20 to 50		°Celsius
Storage Temperature (Ts)				-20 to 50		°Celsius
Humidity				10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Tridonic	On/off		
Rated Power	36	Watts		
Input Current (@ 230V)	0.15	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	1000	mA		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
275Ø	-	83	-	1.06 kg

PHOTOMETRIC DETAILS

Beam Angle	110.5°
------------	--------

