



SPLASH RD



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

SPLASH RD 54W

LED INGROUND LIGHT

- Stainless steel trim corrosion protection
- IP67 strong water resistance.
- IK09 drive-over durability
- Durable toughened glass for safety.
- Seamless inground installation, no obstacles




BL-54-RD

Technical	IK10	IP67	UGR <19	CRI >80
Chip		SMD	-	
Luminous Efficacy (subject to a tolerance of $\pm 10\%$)		100	Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500	Kelvin	
Lifetime		50,000	Hours	
McAdam Binning		3	Step	
Housing				
Body		Stainless Steel Trim	Aluminium Die-cast body	
Lens / Diffuser		Toughened Glass		
Reflector		-		
Mounting		Inground recessed		
Thermal				
Ambient Temperature (Ta)		-20 to 50	°Celsius	
Storage Temperature (Ts)		-20 to 50	°Celsius	
Humidity		10 to 90	RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Control Brand	-	On/off
Rated Power	54	Watts
Input Current (@ 230V)	0.23	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	1050	mA
Output Voltage	21 to 48	VDC
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
320Ø	-	100	295	- kg

PHOTOMETRIC DETAILS

Beam Angle	29°
------------	-----

