



BOLLAX QUADBEAM

 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

BOLLAX QUADBEAM 60W

LED BOLLARD LIGHT

- High Luminous Efficacy - More light output.
- Corrosion-**resistant** body - Ensures long-lasting durability.
- Long life: 50,000+ hrs - Minimal maintenance.
- Quick & easy installation - with accessible mounting design.
- Consistent Performance & Quality - Delivers stable brightness.




BOL-QBM-060

Technical		IK08	IP65	UGR <19	CRI >80
Light Source			SMD		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			Opal Diffuser		
Reflector			-		
Mounting			Surface		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Inventronics	On/off		
Rated Power	60	Watts		
Input Current (@ 230V)	0.26	Amps		
Input Voltage	100 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	1.6	A		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

D	W	H	Cutout	Weight
140	-	2200	-	13 kg

PHOTOMETRIC DETAILS

Beam Angle	320.3°
------------	--------

