Hansagreen LED

BOLLAX QUADBEAM



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

BOLLAX QUADBEAM 75W

LED BOLLARD LIGHT



- ❑ High Luminous Efficacy - More light output.
- ❑ Corrosion-**resistant** body - Ensures long-lasting durability.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ Quick & easy installation - with accessible mounting design.
- ❑ Consistent Performance & Quality - Delivers stable brightness.


BLXQB-BLD-75W-XXXXK

Technical	IK09	IP66	UGR <19	CRI ≥80
Light Source		SMD	-	
Luminous Efficacy (subject to a tolerance of ±10%)		108	Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/5700	Kelvin	
Lifetime		50,000	Hours	
McAdam Binning (SDCM)		3	Step	
Housing				
Body		Aluminium	Die-cast	
Lens / Diffuser		Opal Diffuser		
Reflector		-		
Mounting		Surface		
Thermal				
Ambient Temperature (Ta)		-20 to +50°	Celsius	
Storage Temperature (Ts)		-40 to +80°	Celsius	
Humidity		10 to 90%	RH	

ELECTRICAL CHARACTERISTICS

Rated Power	75	Watts
Input Current (@ 230V)	0.32	Amps
Input Voltage	100 to 240	VAC
Frequency	50 to 60	Hertz
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

D	H	Weight
140	2200	13 kg

PHOTOMETRIC DETAILS

Beam Angle	360°

