



ARC HEMI



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

ARC HEMI 40W

LED POLE TOP LIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Efficient Heat Dissipation – Die-cast aluminum housing
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Modern design – Enhances urban and landscape aesthetics
- ❑ Consistent Performance & Quality - Delivers stable brightness




ARH-PT-40

Technical		IK08	IP66	UGR <19	CRI >80
Light Source			SMD	-	
Luminous Efficacy (subject to a tolerance of ±10%)			120		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			PC Lens		
Reflector			-		
Mounting			Pole		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 95		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF  1-10V 
Rated Power	40 Watts
Input Current (@ 230V)	0.17 Amps
Input Voltage	100 to 240 VAC
Frequency	50 to 60 Hertz
Output Current	1.11 Amps
Output Voltage	17 to 54 VDC
Power Factor	≥0.9

DIMENSIONAL DETAILS



All measurements are in mm

L	W	Pole Dia	Cutout	Weight
510	440	76	-	7.69 Kg

PHOTOMETRIC DETAILS

Beam Angle	109.3°
------------	--------

