



ARC HEMI



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

ARC HEMI 50W

LED POLE TOP LIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Efficient Heat Dissipation – Die-cast aluminum housing
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Modern design – Enhances urban and landscape aesthetics
- ❑ Consistent Performance & Quality - Delivers stable brightness




ARH-PT-50

Technical		IK08	IP66	UGR <19	CRI >80
Light Source			SMD	-	
Luminous Efficacy (subject to a tolerance of ±10%)			130		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			PC Lens		
Reflector			-		
Mounting			Pole		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 95		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	1-10V	
Rated Power	50		Watts
Input Current (@ 230V)	0.21		Amps
Input Voltage	100 to 240		VAC
Frequency	50 to 60		Hertz
Output Current	1.38		Amps
Output Voltage	17 to 54		VDC
Power Factor	≥0.9		

DIMENSIONAL DETAILS



All measurements are in mm

L	W	Pole Dia	Cutout	Weight
510	440	76	-	7.69 Kg

PHOTOMETRIC DETAILS

Beam Angle	109.3°
------------	--------

