



## BOLLAX Z



 +971 65 260 706     sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

# BOLLAX Z 15W

## LED BOLLARD LIGHT

- Uniform and precise lighting distribution
- Quick & easy installation
- Corrosion resistance
- High impact resistant body
- Dust & moisture proof




### BLXL-BLD-15W-XXXXK

Technical		IK09	IP66	UGR <18	CRI >80
Light Source		COB		-	
Luminous Efficacy (subject to a tolerance of ±10%)		92		Lumen / Watt	
Correlated Colour Temperature (CCT)		2700/3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		Aluminium Die Cast			
Lens / Diffuser		Toughened Glass			
Reflector		-			
Mounting		Surface			
Thermal					
Ambient Temperature (Ta)		-20 to 50		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 95		RH(%)	

## ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	15			Watts
Input Current (@ 230V)	0.065			Amps
Input Voltage	220 to 240			VAC
Frequency	50 to 60			Hertz
Output Current	0.416			Amps
Output Voltage	15-42			VDC
Power Factor	≥0.9			

## DIMENSIONAL DETAILS



All measurements are in mm

L	W1	W2	Cutout	Weight
1000	220	120	-	-

## PHOTOMETRIC DETAILS

Beam Angle	94.7°
------------	-------

