



## DOTLUXE RE



 +971 65 260 706     [sales-me@hansagreen.com](mailto:sales-me@hansagreen.com)

 Hamriyah Free Zone Sharjah, UAE.

# DOTLUXE RE 15W

## LED TRACK MOUNTED LIGHT

- High Luminous efficacy - More light output.
- Focused Illumination – Precise directional lighting.
- Long life: 50,000+ hrs - Minimal maintenance.
- Easy Installation – Quick, tool-free mounting.
- Optimized Brightness – PC lens enhances light output.




### DLX-RE-15

Technical		IK02	IP44	UGR <21	CRI >80
Light Source			SMD		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Metal Alloy		
Lens / Diffuser			TIR Lens		
Reflector			-		
Mounting			Track mounting		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

## ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	15	Watts		
Input Current (@ 230V)	0.06	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	375	mA		
Output Voltage	9 to 40	VDC		
Power Factor	>0.95			

## DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
340	117	100	-	0.91 kg

## PHOTOMETRIC DETAILS

Beam Angle	24.8°
------------	-------

