



ECLIPSE



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

ECLIPSE 35W

LED RECESSED SPOTLIGHT

- Precision recessed design
- Low-glare visual comfort
- Durable die-cast body
- Consistent colour rendering
- TIR lens optics




ECL-DL-35

Technical		IK02	IP44	UGR <19	CRI >80
Light Source		COB			
Luminous Efficacy (subject to a tolerance of ±10%)		100		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		Aluminium		Die-cast	
Lens / Diffuser		PC Lens			
Reflector		TIR			
Mounting		Recessed mounting			
Thermal					
Ambient Temperature (Ta)		-20 to 45		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	35	Watts		
Input Current (@ 230V)	0.15	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	0.95	Amps		
Output Voltage	24 to 42	VDC		
Power Factor	≥0.90			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
105Ø	-	150	95Ø	0.6 kg

PHOTOMETRIC DETAILS

Beam Angle	37.3°
------------	-------

