



LUMIBROOK CON



+971 65 260 706 sales-me@hansagreen.com

Hamriyah Free Zone Sharjah, UAE.

LUMIBROOK CON 36W

LED WEATHERPROOF LIGHT

- Quick & easy installation
- Consistent output
- PC diffuser for long life
- Connectable modular design
- Dust & moisture proof




LBK-CON-4F-36

Technical		IK09	IP65	UGR <21	CRI >80
Light Source		SMD			
Luminous Efficacy (subject to a tolerance of ±10%)		120		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		ABS Plastic			
Lens / Diffuser		PC Diffuser			
Reflector		-			
Mounting		Surface			
Thermal					
Ambient Temperature (Ta)		-20 to 45		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 95		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Rated Power	36	Watts
Input Current (@ 230V)	0.15	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	1.2	Amps
Output Voltage	24 to 42	VDC
Power Factor	≥ 0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
1200	74	69	-	1.15 kg

PHOTOMETRIC DETAILS

Beam Angle	113.3°
------------	--------

