



LUMIBROOK SLIM



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

LUMIBROOK SLIM 20W

LED WEATHERPROOF LIGHT

- Quick & easy installation.
- Consistent output.
- PC diffuser for long life.
- Tool-free clips for effortless servicing.
- Dust & moisture proof.




LBK-SLM-4F-20

Technical		IK09	IP65	UGR <21	CRI >80
Light Source			SMD	-	
Luminous Efficacy (subject to a tolerance of $\pm 10\%$)			120		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			ABS Plastic		
Lens / Diffuser			PC Diffuser		
Reflector			-		
Mounting			Surface		
Thermal					
Ambient Temperature (Ta)			-20 to 50		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	20	Watts		
Input Current (@ 230V)	0.086	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	0.55	Amps		
Output Voltage	24 to 42	VDC		
Power Factor	≥ 0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
1200	82	75	-	1.17 kg

PHOTOMETRIC DETAILS

Beam Angle	120.8°
------------	--------

