



LUMIBROOK SLIM



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

LUMIBROOK SLIM 60W

LED WEATHERPROOF LIGHT

- Quick & easy installation.
- Consistent output.
- PC diffuser for long life.
- Tool-free clips for effortless servicing.
- Dust & moisture proof.




LBK-SLM-5F-60

Technical		IK09	IP65	UGR <21	CRI >80
Light Source		SMD			
Luminous Efficacy (subject to a tolerance of ±10%)		120		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		ABS Plastic			
Lens / Diffuser		PC Diffuser			
Reflector		-			
Mounting		Surface			
Thermal					
Ambient Temperature (Ta)		-20 to 50		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 95		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	60			Watts
Input Current (@ 230V)	0.26			Amps
Input Voltage	220 to 240			VAC
Frequency	50 to 60			Hertz
Output Current	0.4			Amps
Output Voltage	144			VDC
Power Factor	≥0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
1500	82	75	-	1.2 kg

PHOTOMETRIC DETAILS

Beam Angle	123°
------------	------

