


LUMINX TL



LUMINX TL 15W

LED RECESSED SPOTLIGHT

- ❑ **Tiltable** Design – Adjustable light focus.
- ❑ Easy installation - **Tool-free** spring-clip installation.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ High Luminous efficacy - More light output.
- ❑ Consistent Performance & Quality - Delivers stable brightness.




LNx-TL-DL-15

Technical			IK02	IP44	UGR <19	CRI ≥80
Light Source				COB		Bridgelux
Luminous Efficacy (subject to a tolerance of ±10%)				100		Lumen / Watt
Correlated Colour Temperature (CCT)				3000/4000/6500		Kelvin
Lifetime				50,000		Hours
McAdam Binning				3		Step
Housing						
Body				Aluminium		Die-cast
Lens / Diffuser				PC Lens		
Reflector				White Reflector		
Mounting				Recessed mounting		
Thermal						
Ambient Temperature (Ta)				-20 to 45		°Celsius
Storage Temperature (Ts)				-20 to 50		°Celsius
Humidity				10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Tridonic	On/off		
Rated Power	15	Watts		
Input Current (@ 230V)	0.06	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	400	mA		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
100Ø	-	100	75Ø	0.3 kg

PHOTOMETRIC DETAILS

Beam Angle	29.3°
------------	-------

