


LUMINX TL



LUMINX TL 20W

LED RECESSED SPOTLIGHT

- ☐ **Tiltable** Design – Adjustable light focus.
- ☐ Easy installation - **Tool-free** spring-clip installation.
- ☐ Long life: 50,000+ hrs - Minimal maintenance.
- ☐ High Luminous efficacy - More light output.
- ☐ Consistent Performance & Quality - Delivers stable brightness.




LNx-TL-DL-20

Technical		IK02	IP44	UGR <19	CRI >80
Light Source		COB		-	
Luminous Efficacy (subject to a tolerance of ±10%)		100		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		Aluminium		Die-cast	
Lens / Diffuser		PC Lens			
Reflector		White Reflector			
Mounting		Recessed mounting			
Thermal					
Ambient Temperature (Ta)		-20 to 45		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 90		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Control Brand	Tridonic	On/off		
Rated Power	20	Watts		
Input Current (@ 230V)	0.08	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	500	mA		
Output Voltage	24 to 42	VDC		
Power Factor	>0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
131Ø	-	118	95Ø	0.4 kg

PHOTOMETRIC DETAILS

Beam Angle	33.9°
------------	-------

