




**NEGOZIO BGX2**



 +971 65 260 706     [sales-me@hansagreen.com](mailto:sales-me@hansagreen.com)

 Hamriyah Free Zone Sharjah, UAE.

# NEGOZIO BGX2

## LED GIMBAL LIGHT

- Low Glare - Low glare via optimized optics.
- Long Life: 50,000+ hrs - Minimal maintenance.
- High Luminous Efficacy - More light output.
- Consistent Performance & Quality - Delivers stable brightness.




### BG2-40

Technical		IK02	IP20	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			Clear glass		
Reflector			Faceted silver		
Mounting			Recessed		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

## ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	2x40		Watts	
Input Current (@ 230V)	0.17x2		Amps	
Input Voltage	220 to 240		VAC	
Frequency	50 to 60		Hertz	
Output Current	1.050x2		Amps	
Output Voltage	24 to 42		VDC	
Power Factor	≥0.95		λ	

## DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
370	185	175	340x150	2.05 kg

## PHOTOMETRIC DETAILS

Beam Angle	18.8°
------------	-------

