



NEGOZIO BGX3



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

NEGOZIO BGX3

LED GIMBAL LIGHT

- Low Glare - Low glare via optimized optics.
- Long Life: 50,000+ hrs - Minimal maintenance.
- High Luminous Efficacy - More light output.
- Consistent Performance & Quality - Delivers stable brightness.




BG3-30

Technical		IK02	IP20	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of $\pm 10\%$)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			Clear glass		
Reflector			Faceted silver		
Mounting			Recessed		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	3x30	Watts		
Input Current (@ 230V)	0.13x3	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	0.83x3	Amps		
Output Voltage	24 to 42	VDC		
Power Factor	≥0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
500	185	175	495x150	3.4 kg

PHOTOMETRIC DETAILS

Beam Angle	31.8°
------------	-------

