



PEBBLE



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

PEBBLE 10W

LED RECESSED SPOTLIGHT

- ❑ **Glare**-Controlled Optics – Comfortable, uniform light.
- ❑ Easy installation - **Tool-free** spring-clip installation.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ High Luminous efficacy - More light output.
- ❑ Consistent Performance & Quality - Delivers stable brightness.




PBL-10

Technical		IK02	IP44	UGR <19	CRI >80
Light Source			SMD		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			PC Lens		
Reflector			Black/White		
Mounting			Recessed mounting		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF PHASE DIMMING 1-10V
Control Brand	Tridonic On/off
Rated Power	10 Watts
Input Current (@ 230V)	0.04 Amps
Input Voltage	220 to 240 VAC
Frequency	50 to 60 Hertz
Output Current	250 mA
Output Voltage	24 to 42 VDC
Power Factor	>0.95

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
146	45	48	137x35	0.2 kg

PHOTOMETRIC DETAILS

Beam Angle	31.4°
------------	-------

