



QUASIMOND



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

QUASIMOND 15W

LED BULKHEAD LIGHT

- Durable & long-lasting
- Quick & Easy Installation
- Smooth and even illumination
- Dust & moisture proof
- Impact-resistant




QM-WL-15

Technical		IK08	IP65	UGR <19	CRI >80
Light Source		SMD			
Luminous Efficacy (subject to a tolerance of ±10%)		100		Lumen / Watt	
Correlated Colour Temperature (CCT)		3000/4000/6500		Kelvin	
Lifetime		50,000		Hours	
McAdam Binning		3		Step	
Housing					
Body		Aluminium Die Cast			
Lens / Diffuser		PC Diffuser			
Reflector		-			
Mounting		Surface			
Thermal					
Ambient Temperature (Ta)		-20 to 50		°Celsius	
Storage Temperature (Ts)		-20 to 50		°Celsius	
Humidity		10 to 95		RH(%)	

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	15		Watts	
Input Current (@ 230V)	0.06		Amps	
Input Voltage	220 to 240		VAC	
Frequency	50 to 60		Hertz	
Output Current	0.4		Amps	
Output Voltage	24 to 42		VDC	
Power Factor	>0.90			

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
215	132	60	-	0.4 kg

PHOTOMETRIC DETAILS

Beam Angle	106.4°
------------	--------

