



ROOKIE RD



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

ROOKIE RD 25W

LED SURFACE DOWNLIGHT

- Flexible** Mounting – Surface or pendant installation options.
- Glare**-Controlled Optics – Comfortable, uniform light.
- Long life: 50,000+ hrs - Minimal maintenance.
- High Luminous Efficacy - More light output.
- Consistent Performance & Quality - Delivers stable brightness.




CL-RD-25

Technical		IK02	IP44	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			Clear Glass		
Reflector			Faceted		
Mounting			Surface/Pendant		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	25	Watts		
Input Current (@ 230V)	0.11	Amps		
Input Voltage	220 to 240	VAC		
Frequency	50 to 60	Hertz		
Output Current	0.7	Amps		
Output Voltage	24 to 42	VDC		
Power Factor	≥0.95			

DIMENSIONAL DETAILS



All measurements are in mm

D	W	H	Cutout	Weight
129Ø	-	155	-	0.7 kg

PHOTOMETRIC DETAILS

Beam Angle	43.8°
------------	-------

