



ROOKIE SQ



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

ROOKIE SQ 35W

LED SURFACE DOWNLIGHT

- ❑ **Flexible** Mounting – Surface or pendant installation options.
- ❑ **Glare**-Controlled Optics – Comfortable, uniform light.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ High Luminous Efficacy - More light output.
- ❑ Consistent Performance & Quality - Delivers stable brightness.




CL-SQ-35

Technical		IK02	IP44	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium Die Cast		
Lens / Diffuser			Clear Glass		
Reflector			Faceted		
Mounting			Surface/Pendant		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING	1-10V	DALI
Rated Power	35			Watts
Input Current (@ 230V)	0.15			Amps
Input Voltage	220 to 240			VAC
Frequency	50 to 60			Hertz
Output Current	0.97			Amps
Output Voltage	24 to 42			VDC
Power Factor	≥0.95			

DIMENSIONAL DETAILS



All measurements are in mm

L	W	H	Cutout	Weight
160	160	164	-	1.48 kg

PHOTOMETRIC DETAILS

Beam Angle	51.6°
------------	-------

