



SILVER LINE




 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

SILVER LINE 10W

LED RECESSED SPOTLIGHT

- ❑ High Luminous efficacy - More light output
- ❑ Narrow Beam – Focused light emission for precise highlighting.
- ❑ Long life: 50,000+ hrs - Minimal maintenance
- ❑ Easy installation - Tool-free spring-clip installation.
- ❑ Consistent Performance & Quality - Delivers stable brightness




PCL-DL-10

Technical		IK02	IP44	UGR <19	CRI >80
Light Source			SMD		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			PC Lens		
Reflector			TIR		
Mounting			Recessed mounting		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Control Brand	Tridonic	On/off
Rated Power	10	Watts
Input Current (@ 230V)	0.04	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	250	mA
Output Voltage	24 to 42	VDC
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
44Ø	-	90	40Ø	0.13 kg

PHOTOMETRIC DETAILS

Beam Angle	28.1°
------------	-------

