



STEFANO



 +971 65 260 706  sales-me@hansagreen.com

 Hamriyah Free Zone Sharjah, UAE.

STEFANO 40W

LED RECESSED DOWN LIGHT

- ❑ **Low Glare** - Low glare via optimized optics.
- ❑ Easy installation - **Tool-free** spring-clip installation.
- ❑ Long life: 50,000+ hrs - Minimal maintenance.
- ❑ High Luminous efficacy - More light output.
- ❑ Consistent Performance & Quality - Delivers stable brightness.




SDL-CB-40

Technical		IK02	IP44	UGR <19	CRI >80
Light Source			COB		-
Luminous Efficacy (subject to a tolerance of ±10%)			100		Lumen / Watt
Correlated Colour Temperature (CCT)			3000/4000/6500		Kelvin
Lifetime			50,000		Hours
McAdam Binning			3		Step
Housing					
Body			Aluminium		Die-cast
Lens / Diffuser			PC Lens		
Reflector			Faceted Reflector		
Mounting			Recessed mounting		
Thermal					
Ambient Temperature (Ta)			-20 to 45		°Celsius
Storage Temperature (Ts)			-20 to 50		°Celsius
Humidity			10 to 90		RH(%)

ELECTRICAL CHARACTERISTICS

Control Option	ON/OFF	PHASE DIMMING 1-10V DALI
Control Brand	Philips	On/off
Rated Power	40	Watts
Input Current (@ 230V)	0.17	Amps
Input Voltage	220 to 240	VAC
Frequency	50 to 60	Hertz
Output Current	1050	mA
Output Voltage	24 to 48	VDC
Power Factor	>0.95	

DIMENSIONAL DETAILS



All measurements are in mm

L/D	W	H	Cutout	Weight
200Ø	-	95	180Ø	0.97Kg

PHOTOMETRIC DETAILS

Beam Angle	67.4°
------------	-------

